

# STRATO-VUE 2 Ellipsoid Aerostat

Specification January 2026

| Category                                | Technical Parameter       | Description / Unit of Measure                           |
|-----------------------------------------|---------------------------|---------------------------------------------------------|
| <b>1. General Characteriscs</b>         | Model / Designation       | <b>STRATO-VUE 2</b>                                     |
|                                         | Purpose                   | Tactical Reconnaissance Aerostat System                 |
|                                         | Construction Type         | The internal pressure maintains the envelope's rigidity |
| <b>2. Geometric Dimensions</b>          | length                    | 3.5 X 3.5 X 2.8 m                                       |
|                                         | Helium Volume             | App 18 m3                                               |
|                                         | Stabilisation             | Polyester mesh (stabilisaon sail)                       |
| <b>3. Masses and Payload</b>            | Gross lift                | App 18 kg                                               |
|                                         | Empty System Weight       | App 7 kg                                                |
|                                         | Maximum Payload Capacity  | 2 kg                                                    |
| <b>4. Operational Performance</b>       | Max Operang Altude        | 100 m                                                   |
|                                         | Max Wind Speed Limit      | 20 km/h                                                 |
|                                         | Operang Temp. Range       | -10 to 60 °C                                            |
|                                         | Daily Helium Leakage      | Up to 1% per day on total volume                        |
| <b>5. Materials &amp; Craftsmanship</b> | Envelope Material         | 100 microns TPU White                                   |
|                                         | Seam Technology           | Ultrasonic Welding (0.2 mm seam)                        |
|                                         | Stabilisation             | Stabilisaon sail                                        |
|                                         | Valve System              | Scoprega 2 stage valve at the back at the low point     |
|                                         | Safety valve              | YES (RX/TX control of the valve)                        |
| <b>6. Tether &amp; Power System</b>     | Tether Line               | 100m 7 mm Polyester (300 kg BS)                         |
|                                         | Tether Power System (TPS) | No (Available on request)                               |
| <b>7. Logistics &amp; Preparation</b>   | Setup / Inflation Time    | Up to 2 hour                                            |
|                                         | Packaging Dimensions      | 1.5 x 1.5 x 1 m                                         |

